

Anti-gravel coat ANTIGRAVITEX**Description:**

This agent, designed for the protection of car bodies, is produced on the basis of high quality synthetic resins, and does not contain any bitumen or asphalts. After drying the fine-grained coat is elastic and resistant to gravel, stones, water, salt, grease and oil. Effectively protects the car body against corrosion. Characterized by soundproofing properties. This product is applied by a special spray gun for thick masses. After drying it can be covered with any type of an external lacquer.

It can be used on the following surfaces:

- Plastic materials
- Wash primer
- Polyester putties by RANAL
- Polyester laminates
- Aluminium
- Steel
- Galvanized steel
- Stainless steel

Nozzle, working pressure:

Apply with a gun for thick masses of 4 mm nozzle and pressure equal to 2-4 bars.

Real level of Volatile Organic Compounds (VOC):

530 g/l

Instruction for use:

Before applying, clean, dry and degrease the surface. Areas not designed for coating should be protected by a tape, covering paper or foil. Before applying, shake the container. Apply 2-3 single coats. Between the applications of the coats wait for about five minutes.

Attention! Do not apply in the temperature below 10°C.

Drying time:

Between 40 and 60 minutes in the temperature of 20°C. After precise drying (60 minutes), external lacquer can be applied.

Thickness of the coat:

About 100 µm for each coat.

Theoretical efficiency:

1 litre of the product is enough for coating the surface of about 4 m², with the thickness of the coat equal to 100 µm.

Colours available:

White, black, grey.

Storage:

To be stored in dry and cool place, away from the sources of light and heat. Storage time of the product in the original package is equal to 12 months in the temperature 20°C.

Health and safety recommendations:

Apply safety data sheet of the particular product.

Packaging:

Capacity:	Package, pieces:	Weight of the carton, kg
500ml (spray)	12	7,50
1 kg	12	13,30
1 L	12	15,50
1,85 kg	6	11,50

This information is based on careful, laboratory research and our long-standing experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.

RANAL Sp. z o.o.