

Sealing mass RANAL**Description:**

This sealing mass is a one-component product designed for protecting welded or soldered areas. The product hardens when the thinner is evaporated in the temperature of 20°C. Dry surface is marked by good elasticity and adhesion to the surface. It does not flow down or leave scratches. It can be covered with any type of acryl lacquer.

It can be used on the following surfaces:

- Plain steel
- Lacquered surfaces
- Polyester laminates

Instruction for use:

Apply on cleaned, degreased and dry surface. To be applied with a hard brush. Recommended temperature of application is between +5 and + 35°C. Product can be removed by acryl thinner or nitro.

Drying time:

Drying time of the coat in the temperature of 20°C is equal to about 7 minutes. After 2 – 3 hours (depending on the thickness of the coat) the surface can be lacquered. Total hardening of 4 mm thick coat results after 24 hours.

Colour:

Grey.

Tools cleaning:

Acryl thinner or nitro.

Storage:

To be stored in dry and cool place, away from the sources of light and heat. Avoid sun exposure. Storage time of the product in the original package in the temperature 20°C is equal to 12 months.

Health and safety recommendations:

Apply safety data sheet of the particular product.

Packaging:

Art.Nr	Capacity, L:	Package, pieces:	Weight of the carton, kg
20432	1	6	14,10

This information is based on careful, laboratory research and our long-standing experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.

RANAL Sp. z o.o.