



# U-Primer 130

## Black moisture curing 1-step glass primer

1

### Description

U-Primer 130 is a black primer specifically designed for the ceramic band on vehicle glass. It ensures the complete protection of the adhesive by creating a barrier against harmful UV rays which can lead to the degradation of the adhesive. It is also an adhesion promoter.

### Areas of Application

U-Primer 130 improve sealant adhesion on glass, ceramic coated glass and on different plastic and metal materials

### Technical data

<b>Appearance</b>	Liquid free from lumps
<b>Colour</b>	Black
<b>Chemical nature</b>	Polyisocyanates
<b>Curing Mechanism</b>	Moisture-curing
<b>Density [g/cc]</b>	0,95 ± 0,02
<b>Drying time [min]</b> (23°C and 50%)	10
<b>Application</b>	felt applicator
<b>Application temperature [°C]</b>	from +10 to +35



DESIGN AND PRODUCTION  
BY CERTIFIED QUALITY SYSTEM  
UNI EN ISO 9001:2008



**NPT** S.r.l.  
NEW POLYURETHANE TECHNOLOGIES  
Via Guido Rossa, 2 - 40088 Crepellano (BO) Italy  
ph. +39 051 98.91.09 - fax. +39 051 98.98.37  
e-mail: [ecosimp@ecosimp.com](mailto:ecosimp@ecosimp.com) - web: [ecosimp.com](http://ecosimp.com)  
P.IVA 0180881098 - C.F. 0185370180



## Application

The surfaces to be treated must be perfectly clean, dry, dust and grease free. Application of U-Primer 130 can only take place once the thorough cleaning of the bonding area with U- Activator has been completed. Shake bottle well before application (for at least 1 min.) till the noise of the metal balls contained in the bottle can be heard. Close immediately after use as product evaporates very quickly. Ensure that primer is tack-free dry before proceeding. An open time of longer than 24 hours necessitates reactivating the primer

## Coverage

U-Primer 130 has consumption of about 150 g/m<sup>2</sup>.

## Personal protective measures

Avoid skin contact using latex, rubber or polyethylene gloves.

## Packaging

Aluminum bottle 30 ml:	25 bottles per box
Aluminum bottle 250 ml:	12 bottles per box
Aluminum bottle 1 Lt	8 bottles per box

## Storage

U-Primer 130 can be stored for 12 months in its original packing at 10°- 25°C. *The product is flammable.* Keep away from heat sources, store in a dry and well-ventilated area in its original packaging. Keep out of the reach of children.

## General Information

The information contained in this technical data sheet is to the best of our knowledge correct, being based on our knowledge and experience to date and cannot be used as a guarantee, due to the various different materials present on the market and the fact that the application conditions are not under our direct control and supervision. NPT srl, however, guarantees constant product quality. NPT srl, has the right to modify or up-date this technical data sheet according to requirements. Customers are kindly requested to verify that they are in possession of the latest version.

ALWAYS CONSULT THE MATERIAL SAFETY DATA SHEET BEFORE USING THE PRODUCT.

N. P. T. Srl - Guido Rossa, 2 40056 Crespellano (Bo) - ITALY Phone +39.051.969109 • Fax +39.051.969837



DESIGN AND PRODUCTION  
BY CERTIFIED QUALITY SYSTEM  
UNI EN ISO 9001:2008

