

# Adhesive for windscreen

SECTION 1: SUBSTANCE/MIXTURE IDENTIFICATION AND MANUFACTURER/SUPPLIER IDENTIFICATION

# 1.1. Product identification

Adhesive for windscreen

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Adhesive for windscreen is a one-component polyurethane product characterized by good adhesion, polymerizing under the influence of humidity. Instructions for use: clean and degrease the surface. Glass surfaces should be treated with a silicon remover and a primer. After drying the primer, apply the product.

#### 1.3. Data of the safety data sheet supplier

#### Przedsiębiorstwo RANAL Sp. z o.o.

UI. Warszawska 36a PL 42-240 Rudniki Tel: +48 34 329-45-03 Fax: +48 34 320-12-16

## Person responsible for the safety data sheet

e-mail: ranal@ranal.pl

# 1.4. Emergency telephone

+48 34 329-45-03 (from 7:30 am. to 3:30 pm.)

#### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

This mixture is classified as dangerous according to EC Directive 1999/45/EC. Major adverse effects: see sections 9 to 12.

#### 2.2. Label elements:

Contains: styrene Signs:



Risk symbol: Xn Harmful

Hazards: harmful (#) - R-phrases: R42 (\*) - S-phrases: S23, S36, S45, S60 (\*) Contains isocyanates. See the information submitted by the manufacturer. (\*) See section 16 for full text of R-phrases, and S- phrases.

#### 2.3 Other hazards

None.

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1. Substances

N.AV.

#### 3.2. Mixtures

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive

67/548/EEC or Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List

Name	Registr ation	CAS No	EINECS No	Class. 67/548/CE	Class. CLP (**)	Conc. %

# MATERIAL SAFETY DATA SHEET Date of issue: 09.08.2013

Updating date : 09.08.2013



# Adhesive for windscreen

	No			(**)		
1,2- Benzenedicarboxylic acid, di-C8-10-alkyl esters [5]	N.AV.	71662-46-9	275-809-7	-	-	> 10,0-< 20,0
Diisononyl phthalate [5]	N.AV.	28553-12-0	249-079-5	-	-	> 1,0 - <10,0
Hexamethylene-1,6- diisocyanate homopolymer [1]	N.AV.	28182-81-2	500-060-2	Xi, R43	H317	> 1,0 - < 5,0
Diphenylmethane-4,4'- diisocyanate [1] [2]	N.AV.	101-68-8	202-966-0	Xi, Xn, R20, R36/37/38, R40, R42/43, R48/20	H315, H317, H319, H332, H334, H335, H351, H373	> 0,1 - < 1,0

[1] Substance that presents a danger to the environment or health.

[2] Substance with a workplace exposure limit.

[3] PBT-Substance.

[4] vPvB-Substance.

[5] Ingredient voluntarily declared.

(\*\*)See Section 16 for full text of R-phrases and H-statements.

Full text of the phrases identifying the types of hazard and R phrases provided in section 16.

# **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, lead in a safe place and seek medical advice.

Routes of exposure:

- Skin contact: remove with a cloth or paper and wash with soap and water. In case of persistent irritation, or in the case of tissue damage, consult a doctor.

<u>- Eye contact</u>: wash with running water for several minutes, holding the eyelids open. If symptoms persist, call a physician.

- Ingestion: Do NOT induce vomiting. Never give anything by mouth if victim is unconscious. Call for medical help immediately.

- Inhalation: If you feel unwell move to a fresh air, if symptoms persist, consult a doctor.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Skin contact: N.AV.
- <u>Eve contact:</u> N.AV.
- Ingestion: N.AV.
- Inhalation: N.AV.

4.3 Indication of any immediate medical attention and special treatment needed

N.AV.

#### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

- Appropriate extinguishing media: water spray, foam, CO2 and powder.

- Information about suitable extinguishing media: preferred foams resistant to alcohol.

- Extinguishing inappropriate: do not use direct water stream.

- Indicate whether certain methods of extinction are inadequate in a specific situation related to substance: none in particular.

#### 5.2 Special hazards arising from the substance or mixture

With the fire, poisonous gases may be formed. The product is not explosive but it is possible the formation of mixtures of explosive air/vapor.

#### **5.3 Advice for fire-fighters**

Do not inhale gases produced by fire. Wear breathing apparatus with an independent source of fresh air. Cool containers or tanks exposed to fire with water spray.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: wear gloves and protective clothing, safety glasses and protection for the breathing apparatus

(SCBA). Avoid sources of ignition.

Strona: 2 z 7



# Adhesive for windscreen

#### 6.2 Environmental precautions

Do not allow product contaminate the sewage or any water course. In case of accidental release alert the relevant

authorities

# 6.3 Methods and material for containment and cleaning up

- Recommendations on how to contain a spill: contain and absorb the material with inert absorbent barriers. - Recommendations on how to clean a spill: collect mechanically picking up and place in appropriate containers before

you start the disposal of the waste regulation.

# 6.4 Reference to other sections

Treat material as prescribed in section 13.

#### SECTION 7: HANDLING AND STORAGE OF SUBSTANCES AND MIXTURES

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor and spray mist arising from application of this mixture. Smoking, eating and drinking should be prohibited in scope. Comply with the regulations regarding health and safety as provided by law. Do not allow to enter drains or watercourses. See also section 8.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep containers closed. Protect from water and sources of ignition. For more storage information follow the instructions on the label.

#### 7.3 Specific end use(s)

N.AV. refer to section 1.2.

#### SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION MEASURES

#### 8.1. Control parameters

Components with exposure limits 4,4' - methylenediphenyl diisocyanate (n° CAS: 101-68-8; n° EC: 202-966-0).-Limit value for occupational exposure: National (IT): TLV-TWA = N.AV.TLV-STEL = N.AV.ACGIH 2009: TLV-TWA = 0,005 ppm.TLV-STEL/C = N.AV.- Biological limit values: Valori limite biologici: N.AV.

DNEL: N.AV. PNEC: N.AV.

#### 8.2 Exposure controls

Individual protection measures, such as personal protective equipment:

Eye protection/face: use glasses to protect against splash of liquids.

Skin Protection: no special precaution must be adopted for normal use, wear appropriate clothing.

Hand protection: use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicalsand micro-organisms. Acceptable nitrile gloves. Respiratory protection: when atmospheric levels may exceed the exposure guideline, use the self-breathing apparatus.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### General information

- Appearance:	thixotropic paste								
- Odour:	sweet								
- Odour threshold:	N.AV.								
9.1 Information on basic physical and chemical properties									
- pH:	N.AV.								
- Melting point/freezing point (92/69/EEC, A1):	N.AV.								
- Initial boiling point and boiling range (92/69/EEC, A2):	N.AV.								
- Flash point:	> 100°C estimated.								
- Evaporation rate:	N.AV.								
- Flammability (solid, gas):	N.AV.								
- Explosive limits:	N.AV.								
- Vapour tension:	N.AV.								
- Vapour density (air=1):	N.AV.								
- Relative density (92/69/EEC, A3):	1,36 g/ml (20°C)								
- Solubility in water (92/69/EEC, A6):	N.AV.								
- Solubility in organic solvents:	N.AV.								
- Partition coefficient: n-octanol/water:	N.AV.								
Strona: 3 z 7									

# MATERIAL SAFETY DATA SHEET Date of issue: 09.08.2013

Updating date : 09.08.2013



#### Adhesive for windscreen

- Auto-ignition temperature:

- Decomposition temperature:
- Viscosity:
- Explosive properties:
- Oxidising properties:
- 9.2 Other information:

- VOC 0 g/l.

# SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity

N.AV.

**10.2 Chemical stability** 

Stable under recommended storage and handling conditions (see section 7). **10.3 Possibility of hazardous reactions** 

None under recommended storage and handling conditions

#### **10.4 Conditions to avoid**

Some components of this product can decompose at elevated temperatures. Avoid moisture.

10.5 Incompatible materials

Oxidizing agents, acids, bases, alcohols, amines, water, ammonia, metal compounds and moist air. **10.6 Hazardous decomposition products** 

Combustion can give rise to the formation of dangerous products.**SECTION 11: TOXICOLOGICAL INFORMATION** 

There are no data available on the mixture itself. Set out below is the toxicological information relating to the main substances in the mixture. Hazardous effects to health from exposure to the mixture: see Sections 2 and 4. **11.1 Information on toxicological effects** 

# • Diisononyl phthalate:

- Acute toxicity, dermal toxicity: LD50 rabbit > 3160 mg/kg. Metodo OECD TG 402.

- Acute toxicity, by oral route: LD50 rat => 10000 mg/kg. Directive 84/449/EEC method B.1

• Hexamethylene-1,6-diisocyanate homopolymer:

Acute toxicity, dermal toxicity: LD50 rabbit > 5000 mg/kg. Metodo OECD TG 402. Test on major components.
Acute inhalation toxicity: LC50 rat = 4,63 mg/l, 4 h, (Atm. dust / mist). Method OECD TG 403. Test on major components.

- Acute toxicity, by oral route: LD50 rat => 5000 mg/kg. Directive 84/449/EEC method B.1

# • 4,4' – methylenediphenyl diisocyanate:

- Acute toxicity, by oral route: LD50 rat => 2000 mg/kg. Directive 84/449/EEC method B.1 - Tests on comparable product.

- Acute toxicity, dermal toxicity: LD50 rabbit => 9400 mg/kg. Method OECD TG 402 - Tests on similar product. - Acute inhalation toxicity: LC50 rat = 0,368 mg/l, 4 h,> 2,24 mg/l, 1h. (Atm. dust / mist). Method OECD TG 403 - Substance tested in forms other than commercial and in which is supposed to be used rationally. It therefore justifies a different classification of the acute inhalation toxicity.

- Primary skin irritation: rabbit = irritant, causes skin irritation. Method OECD TG 404 – Tests on comparable product.

- Primary irritations of the mucous membranes: rabbit = non-irritating. Method OECD TG 405 – Tests on comparable product.

- Skin sensitization according to Buehler (skin test): guinea pigs = negative, does not cause skin sensitization. Method OECD TG 406.

- Skin sensitization (LLNA (Local Lymph Node Assay)): mouse = positive. Method OECD TG 429.

- Respiratory sensitization: guinea pigs = positive, may cause sensitization by inhalation.

- Subacute, subchronic and prolonged toxicity: rat NOAEL = 0,2 mg/m3, 1 mg/m3LOAEL; irritation to the nasal cavity and lungs. Method OECD TG 453 - Tests on similar product.

- Carcinogenicity: rat (inalativo) = if applicable of tumors in the higher dose (6 mg/m3). Method OECD TG 453 - Tests on similar product.

- Reproductive toxicity / teratogenicity: rat = NOAEL (teratogenicity) 12 mg/m3NOAEL (maternal) 4 mg/m3 NOAEL (developmental toxicity) 4 mg/m3, did not show teratogenic effects in animal experiments. Method OECD TG 414 – Tests on similar product.

- Genotoxicity in vitro test Salmonella / microsome (Ames test) = negative. Method OECD TG 471 – Tests on comparable product.

- Genotoxicity in vivo micronucleus assay, rat = negative. Method OECD TG 474.

- Specific toxicity in the target organ (single exposure): = inalativo may irritate the respiratory tract.

- Specific toxicity in the target organ (repeated exposure): = inalativo can cause damage to organs in the event of prolonged or repeated exposure.

CMR Rating:

Carcinogenicity: product is suspected to cause cancer if inhaled (Carc 2).

Mutagenicity: In vitro and in vivo studies showed no mutagenic effects. Based on the data available data, the

N.AV. N.AV. 50000-250000 cps (23°C) [Method: plate/cone] N.AV. N.AV.

133.35 g/l (10,5%) (#)

MATERIAL SAFETY DATA SHEET Date of issue: 09.08.2013

Updating date : 09.08.2013



# Adhesive for windscreen

classification criteria are not met.

Teratogenicity: Did not show teratogenic effects in animal experiments. On the basis of available data, the classification criteria are not met.

Toxicity to reproduction/fertility: Based on the available data, the classification criteria are not satisfied. <u>Toxicological evaluation:</u>

Acute Effects: harmful if inhaled. The product causes irritation of eyes, skin and mucous membranes. Sensitization: may cause sensitization by inhalation and skin contact.

Additional information:

particular characteristics/effects: If there is a danger of overexposure, depending concentration, irritation of the eyes,

nose, throat and respiratory tract. Possible the delayed appearance of disorders and development of a form of hypersensitivity (disorders breathing, coughing, asthma). In the case of people who are hypersensitive reactions may occur as early concentrations of isocyanate very low, even below the TLV value. In case of contact prolonged, skin irritating and dehydrating effects are possible.

# SECTION 12: ECOLOGICAL INFORMATION

Use according to standards of good practice and avoid release to the environment (see also sections 6,7,13,14, 15). There are no ecotoxicological data on the mixture itself. Set out below is the toxicological information relating to the main substances in the mixture.

#### 12.1 Toxicity

• 1,2-Benzenedicarboxylic acid, di-C8-10-alkyl esters:

- Acute toxicity for daphnia (EC50): Daphnia magna (water flea), 48h. = > 5,8 mg/l. Method OECD TG 202.

• Hexamethylene-1,6-diisocyanate homopolymer:

- Acute and prolonged toxicity to fish (NOEC): Danio rerio (zebra fish), 96h. = > 100 mg/l.

- Acute toxicity for daphnia (NOEC): Daphnia magna (water flea), 48h. = > 100 mg/l.

- Acute toxicity to algae (ErC50): Scenedesmus sp., 72h. (Inhibitor of growth) => 1000 mg/l. Method OECD TG 201

- Acute bacterial toxicity (EC50): activated sludge, 3h. (Inhibitor of growth) = > 1000 mg/l.

4,4' – methylenediphenyl diisocyanate:

- Acute toxicity to fish (LC50): Danio rerio (zebra fish), 96h. = 1000 mg/l. Method OECD TG 203 - Tests on similar product.

- Acute toxicity for daphnia (EC50): Daphnia magna (water flea), 24h. => 1000 mg/l. Method OECD TG 202 - Tests on similar product.

- Chronic Toxicity to Daphnia: Daphnia magna (water flea), 21d, NOEC (reproduction) => 10 mg/l. Method OECD TG 202 - Tests on similar product.

- Acute toxicity to algae (ErC50): Scenedesmus subspicatus, 72h. (Inhibitor of growth) => 1640 mg/l. Method OECD TG 201 - Tests on similar product.

- Acute bacterial toxicity (EC50): activated sludge, 3h. (Inhibitor of respiration) => 100 mg/l. Method OECD TG 209 - Tests on similar product.

- Toxicity to soil dwelling organisms: Eisenia fetida (earthworm), 14 d NOEC (mortality) => 1000 mg/kg. Method OECD TG 207 - Tests on similar product.

- Toxicity to terrestrial plants: Avena sativa (oats), 14d NOEC (germination) => 1000 mg/kg, Avena sativa (oats), 14d NOEC (growth rate) => 1000 mg/kg; Lactuca sativa (lettuce), 14d NOEC (germination) => 1000 mg/kg; Lactuca sativa (lettuce), 14d NOEC (growth rate) => 1000 mg/kg. Method OECD TG 208 - Tests on similar product.

Ecotoxicological assessment:

Acute aquatic environment: based on the available data, the classification criteriaare not satisfied.

Chronic toxicity to the aquatic environment: there is no evidence of chronic aquatic toxicity.

Bitoxicity data on soil: is not expected adsorption to soil. The substance is evaluated as not critical for soil organisms.

Impact on the treatment of waste: due to the low toxicity to bacteria in biological purification plants there is no risk of yield reduction treatment.

#### 12.2 Persistence and degradability

1,2-Benzenedicarboxylic acid, di-C8-10-alkyl esters:

Biodegradability: 76%, 28d, readily biodegradable. Metodo OECD TG 303A.

Diisononyl phthalate:

Biodegradability: 74%,28d. Ultimately biodegradable. Method OECD TG 301C. >99%, 28d. Ultimately biodegradable.

Method OECD TG 302A.

Photodegradation: phototransformation in air, half-life (indirect photolysis) = 0,7 d. Estimated.

Hexamethylene-1,6-diisocyanate homopolymer:

Biodegradability: 0%, 28d, not inherently biodegradable.

• 4,4' – methylenediphenyl diisocyanate:

Biodegradation: 0%, 28d, or not inherently biodegradable. Method OECD TG 302C – Tests on similar product. Stability in 'water: hydrolysis half-life = 20h. at 25 ° C, the substance is rapidly hydrolyzes in water – Tests on similar product.



### Adhesive for windscreen

Photodegradation: phototransformation in air, half-life (indirect photolysis) = 0,92 d., as a result of evaporation or exposure to the air, the product is moderately degraded via photochemical processes. Method SRC - AOP (calculation). Volatility (Henry's law constant): calculated value =  $0,0229 \text{ Pa}\cdot\text{m3/mol}$ , the substance should be classified as slightly volatile in water.

## 12.3 Bioaccumulative potential

• 1,2-Benzenedicarboxylic acid, di-C8-10-alkyl esters:

Bioaccumulation (BCF): < 100. Bioconcentration potential is low.

• *Diisononyl phthalate:* Bioaccumulation (BCF): < 100. Bioconcentration potential is low.

• 4,4' – methylenediphenyl diisocyanate:

Bioaccumulation (BCF 200): Cyprinus carpio (Carp), 28d, concentration = 0,00008 mg/l, it is not to be expected the accumulation in aquatic organisms.

#### 12.4 Mobility in soil

• Diisononyl phthalate:

Expected to be relatively immobile in solil (Koc >5000).

Partition coefficient organic carbon / water in soil (Koc): >5000 Estimated.

• 4,4' – methylenediphenyl diisocyanate:

The mobility is limited by the transformation into a solid insoluble by reaction with humidity and CO2 emissions. 12.5 Results of PBT and vPvB assessment

The components of the mixture, based on the information available, do not meet the criteria vPvB and PBT.

#### 12.6 Other adverse effects

None.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Product must be disposed of in compliance with the proper local and statutory regulations with regard to waste Recover if possible. Operate according to local and national regulations: 91/156/EEC, 91/689/EEC, 94/62/EEC. Disposal of uncured material (according to Directive 2000/532/EC):

waste code EWC 080409 \* - adhesives and sealants containing organic solvents or other dangerous substances. Disposal of hardened product (according to Directive 2000/532/EC):

EWC waste code 080410 - waste adhesives and sealants other than those mentioned in 080409 \*.

Empty containers must be disposed of or recycled.

Containers containing uncured product are hazardous wastes.

# **SECTION 14: TRANSPORT INFORMATION**

Not classified as dangerous under transport regulations.

#### 14.1 UN number N.AP. 14.2 UN proper shipping name

- N.AP.
- 14.3 Transport hazard class(es)
- N.AP.
- 14.4 Packing group
  - N.AP.
- 14.5 Environmental hazards N.AP
- 14.6 Special precautions for user Not dangerous for transport.

  - Irritating to skin or eyes.
  - Protect from moisture.
  - Keep away from foodstuffs, acids and alkalis.
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
  - N.AP.

Additional information for Transport in accordance with IMDG, ADR/RID and ICAO/IATA

- ADR / RID: non-dangerous goods.

- ADN: non-dangerous goods.
- IATA: non-dangerous goods.
- IMDG: Not dangerous goods.

# **SECTION 15: REGULATORY INFORMATION**



# Adhesive for windscreen

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Commission Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH); Directive 67/548/EEC (Classification, packaging and labelling of dangerous substances) and subsequent amendments; Directive 1999/45/EC (Classification, packaging and labelling of dangerous preparations) and subsequent amendments; Regulation (EC) No 1907/2006 (Reach); Regulation (EC) No 1272/2008 (CLP); Regulation (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures. Commission Directive 92/69/EEC of 31 July 1992 adapting to technical progress for the seventeenth time Council Directive 67/548/EEC on the approximation of laws, regulations and administrative provisions relating to the classification, packaging and labelling of dangerous substances The "Threshold Limit Values" of the substances are taken from: a) Italian legislation: Decree 9 April 2008, n. 81 - Appendix XXXVIII and XLIII, 3 August 2009 Legislative Decree no. 106 - Annex XXXVIII; b) EU Legislation: Directive of 2009/161/CE 17dec. 2009; c) the substances not listed by the National legislation and by the EU Legislation are taken from the volume A.C.G.I.H 2009 "Threshold Limit Value (TLV's) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs) "[Source Federchimica -Italian National Association of Chemical Industry: "Threshold limit values and biological indices of exposure to the Risks related to chemicals in the workplace "2010 edition]. Other requirements, restrictions and ban regulations: none

# 15.2 Chemical Safety Assessment

N.AV.

# **SECTION 16: OTHER INFORMATION**

Full text of R-phrases, Hazard Statements-h AND S-phrases appearing in section 2 and 3:

H225 - Highly flammable liquid and vapor.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H331 - Toxic if inhaled.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

R20 - Harmful by inhalation.

R36/37/38 - Irritating to eyes, respiratory system and skin.

R40 - Limited evidence of a carcinogenic effect.

R42/43 - May cause sensitization by inhalation and skin contact.

R43 - May cause sensitization by skin contact.

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.

S23 - Do not breathe gas / fumes / vapor / spray

S24 - Avoid contact with skin.

S37 - Wear suitable gloves.

S45 – In case of accident or if you feel unwell, seek medical advice imemdiately (show the label where possible).

S60 – This material and its container must be disposed of as hazardous waste.

The information contained in this Safety Data Sheet is based on the present state of knowledge and current national legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and

obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. This sheet replaces all previous versions.

#### Bibliography

ESIS – European chemical Substances Information System - Joint Research Centre;

Federchimica – Book series of the Committee for Substances Safety , No. 2 "THE MSDS Part 2 - Examples of Safety Data

Sheet of a substance and a mixture prepared according to Regulation (EU) 453/2010, July 2010". **Acronyms** 

ACGIH: American Conference of Governmental Industrial Hygienists.

**ADN**: european Agreement concerning the international carriage of Dangerous good by iNland goods.

**ADR**: Agreement concerning the international carriage of Dangerous goods by Road.

BCF: Bio Concentration Factor.

Strona: 7 z 7

MATERIAL SAFETY DATA SHEET Date of issue: 09.08.2013

Updating date : 09.08.2013



# Adhesive for windscreen

CLP: Classification, Labelling and Packaging EC50, EC10: Effective Concentration of a substance that causes 50% or 10% of the maximum response. DNEL: derived no effect level ErC50: Effective Concentration of a substance that causes a 50% reduction in the growth rate. EWC: European Waste Catalogue. **IATA**: international air transport association. IBC, code : International Code for the Construction and Equipment of ships carrying dangerous chemical in Bulk. **IMDG**: International maritime dangerous goods. Koc: partition coefficient soil / water. LC 50: Lethal Concentration for 50% of individuals. LD 50: Lethal Dose for 50% of individuals. OECD: Organisation for Economic Co-operation and Development: Guideline for Testing of Chemicals. MARPOL73/78: Convenzione internazionale per la prevenzione dell'inquinamento causato da navi 1973, come modificata dal protocollo del 1978. NOEC: No Observed Effect Concentration. **PBT**: Persistent, bioaccumulative and toxic. **PNEC**: Predicted no effect concentration. RID: Règlement concernent le transport International ferroviaire des marchandises Dangereuses (Regulation concenring the International carriage od Dangerous goods). STEL: short term exposure limit. TLV: threshold limit value. **TWA**: Time Weighted Average. **UE**: Unione Europea. **vPvB**: Very persistent very bioaccumulative. Decoding: (#) = This symbol indicates that the information has been updated to the review date.

N.AV. = Not available.

N.AP = Not applicable.

[...] = Bibliographic reference.